

Polar[®]

Dynamic Sand

SCUFF-RESISTANT SHORT-TERM POP SOLUTIONS

Polar[®] Dynamic Sand is designed for eye-catching textured short-term graphics that instantly attract attention. Its removable, non-damaging adhesive makes Polar[®] Dynamic Sand ideal for broad range of general signage applications, including posters, retail displays and exhibition graphics. Polar[®] Dynamic Sand also offers excellent indoor and outdoor durability with a 2 year lifespan for exterior applications.

- 7 MIL THICKNESS AND TEXTURED SCUFF RESISTANT SURFACE ELIMINATES THE NEED TO LAMINATE

7.0
mil

Textured White
Monomeric
PVC

■
Matte



(Eco) Solvent
Latex
UV



Removable
Solvent Acrylic
(Pressure Sensitive)



Widths up to 60 in



INTERIOR & EXTERIOR
(6 months removability)



APPLICATIONS

SCHOOLS

HOSPITALS

RETAIL ADVERTISING

SUPERMARKETS

RESTAURANTS

DRYTAC[®]

ADHESIVE SCIENCE

www.drytac.com

Polar[®]

Dynamic Sand

Polar[®] Dynamic Sand is a 7 mil (175µ) printable, matte white PVC film with a removable, solvent pressure sensitive acrylic adhesive protected by a 2 side PE coated release liner. The textured emboss on the film provides excellent scuff-resistance.

- IDEAL FOR SHORT-TERM INDOOR OR OUTDOOR GRAPHICS
- EXCELLENT SCUFF-RESISTANCE THANKS TO THE MATTE SAND TEXTURE OF POLAR DYNAMIC SAND
- 7 MIL THICKNESS AND TEXTURED SCUFF RESISTANT SURFACE ELIMINATES THE NEED TO LAMINATE

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

Please Note: Polar Dynamic Sand is not slip rated and also not recommended for wall mural paneling.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2021 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Textured Matte White PVC
Adhesive	Removable Solvent Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated Liner

PRODUCT CHARACTERISTICS

Film Thickness	7.0 mil (175µ) 8.4 mil
Adhesive Layer	1.4 mil (35µ) (210µ)
Fire Rating	B1 (DIN 4102-1)
Application Temperature	>-4°F (-20°C)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC[®]

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com