

# ReTac®

## Textures

ReTac® Textures can add depth and visual appeal to static, flat images with its embossed finish. With ReTac® on the back, eye-catching graphics printed on ReTac® Textures can easily be removed and repositioned multiple times without the worry of adhesive residue being left behind. This phthalate-free film can be easily applied, re-positioned and removed without surface damage or loss of adhesion. Available in Canvas, Linen, Sand and Woodgrain finishes.

- IDEAL FOR INTERIOR PROMOTIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

**6**  
mil

White  
Phthalate-Free  
Polymeric  
PVC



Matte



(Eco) Solvent  
Latex  
UV



ReTac® ultra removable  
and re-positionable  
adhesive



Widths up to 54 in



**INTERIOR AND EXTERIOR**  
(2 YEAR REMOVABILITY EXTERIOR)

**ADDS VISUAL INTEREST TO ANY PRINT**

**WOODGRAIN**

**LINEN**

**CANVAS**

**SAND**

## APPLICATIONS

Smooth Flat Surfaces  
Point Of Sale Graphics  
Interior Décor  
Decals & Stickers

**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

## Textures

ReTac® Textures is a 150µ (6 mil) printable, matte white phthalate-free polymeric PVC film with ReTac® ultra removable adhesive. It has an embossed finish that adds depth and visual appeal to static, flat graphics. The texture helps draw attention to your image or message in a distinct and creative way.

- RETAC® TEXTURES IS A PHTHALATE-FREE FILM.
- IDEAL FOR WALL GRAPHICS, CUSTOM WALL MURALS, INTERIOR DÉCOR, RETAIL DISPLAYS, TRADE SHOW GRAPHICS AND SIGNAGE, AND TEXTURED LABELS.

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal, for more information please contact your local representative.

**For more information, performance and warranty guidelines please contact your local Drytac office.**

© 2021 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

03082021

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Embossed Matte White Polymeric PVC
<b>Adhesive</b>	ReTac® ultra removable and re-positionable adhesive technology
<b>Release Liner</b>	143 gsm 2 Side PE Coated, 1 Side Solventless Siliconised Fine Paper

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	6 mil (150µ)   7 mil (175µ)
<b>Adhesive Layer</b>	1 mil (25µ)   (175µ)
<b>Outdoor Durability</b>	5 years; 2 years removability
<b>Fire Ratings</b>	Class C-s1-d0 (EN-13501) Class 1 or A (ASTM E-84) PASS (CAN/ULC-S102)
<b>Slip Ratings</b> (ReTac Textures Sand) <small>*for short-term indoor floor applications only</small>	Moderate Slip Potential (EN 13036-4) Passed (ANSI A137.1/ A326.3) Dry: 58 Wet: 29 (AS HB198:2014 (AS/AZS 4586))
<b>Application Temperature</b>	>41°F (5°C)
<b>Service Temperature Range</b>	-40°F to 120°F (-4.4°C to 48.9°C)
<b>Shelf Life</b>	2 years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### INSTALLATION RECOMMENDATION

Please see Wall Graphic Installation & Removal Instructions for further details.  
The surface must be clean and smooth & free of defects before application.

**DRYTAC®**  
**ADHESIVE SCIENCE**

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013