

100% PVC-free / phthalate-free substrate featuring a grey back-side that prevents translucency and shadowing. This material is ideal for pop-up displays, banner stands, x-frame displays, or any indoor / outdoor close viewing applications that require complete opacity. EcoVantage Greyback is compatible with solvent, eco-solvent, UV, Latex and screen printing and available in widths from 54" to 126".

Material Details

CHARACTERISTICS	TEST	METRIC	ENGLISH
Composition	DIN 60001, D7641	100% Polyester	
Total Weight	DIN EN ISO 2286-2 ASTM D751	260 g/m ²	7.6 oz./yd ²
Denier	DIN EN ISO 2060, ASTM D 1907	500 x 500	
Tensile Strength	DIN EN ISO 1421	1650 x 1500 N/5cm	189 x 171 lbs/in
Tear Strength	DIN 53363	260 x 265 N	58 x 60 lbs
Fire Resistance	NFPA 701		

Applications

	Pop-Up Displays	Banner	Roll-Up Displays	Blockout	Scrolling Signs	X-Displays	Trade Show Displays
Applications	■	■	■	■	■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■		

Available Sizes

Metric (m)	English (inches)
1.37, 1.60, 3.20	54", 63", 126"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)